

TATUNG V42EMGI

The Depth of Visual Sensation... The Tatung 42" 1920*1080 HD Widescreen LCD TV

Features

- Comply Europe PAL/SECAM system, B/G, D/K, I, L/L'
- Compatible with all 576i/576p/720p/1080i, even 1080P
- Universal video color system, PAL / SECAM / NTSC
- Progressive Scan, 2:2 Pull Down
- 3D de-interlacer & Comb Filter
- Auto Program System & Searching (APS)
- Auto Volume & Power Control
- Teletext 255 pages

System Spec.

- Resolution: 1920 x 1080
- Contrast Ratio: 1200:1
- Response Time: 6.5 ms
- Brightness: 500 cd/m²
- HDMI/DVI Connectivity



Items	Model Name	V42EMGI (EU Model)
Panel	Aspect Ratio	16:9
	Resolution	1920 x 1080
	Display Area (opening) H x V	930.24 mm x 523.26 mm
	Display colors	16,777,216 colors
	Contrast Ratio	1200 : 1 (typ.)
	Brightness (center)	500 cd / m ² (typ.)
	Viewing Angle (CR>10)	176° Hor. / 176° Ver. (typ.)
	Response Time (BTW)	6.5ms (typ.)
TV function	Broadcasting System	Analog : PAL / SECAM
	Receiving Channel	Analog : B / G, D / K, I and L / L'
	Sound System	Analog : NICAM / A2 (IGR)
	Resolution	Analog : 625i
	Data Broadcasting	Teletext 255 pages (FLOF / TOP) , Auto Program Searching (APS)
Video Input	Video Color System	PAL / SECAM / NTSC
	AV1 (SCART)	21-pin Scart (RGB / CVBS) x 1
	AV2 (SCART)	21-pin Scart (RGB / CVBS/ SVHS) x 1
	AV3 (CVBS, Y/C)	Composite (RCA jack) x 1 S-Video x 1
	AV4 (Component)	Y Pb Pr (720p / 1080i , HDTV ready) x 1
	AV5 (HDMI)	HDMI 19 pin x 1 (HDMI 1.1 / HDCP 1.1)
PC Input (analog)	DVI-D Connection	DVI-D x 1
	VGA Connection	D-Sub 15 pin x 1
	Scanning Frequency	f _H = 31.5 ~ 60KHz / f _V = 56 ~ 75Hz
Audio Input	Audio 1	SCART (build-in) x 2
	Audio 2	Composite x 1 S - Video x 1 Component x1
	Audio 3	PC x 1
	Video Output	SCART 1 TV SCART 2 TV / CVBS Composite (RCA jack) TV
	Audio Out	Speaker (build-in)
Without Accessories		Left / Right / Subwoofer
SP/DIF		HDMI loop through
Feature	OSD Language	English, French , German , Spanish , Italian ,Finnish , Swedish, Dutch, Demark, Norway
	Function Keys	Power , Source , Menu , Up/Down(Channel) , +/- (Volume) , ARC/EXIT .
	Video Performance	3D Comb-filter , 3D De-interlace, Advanced Chroma Processing, Video Enhance, Noise Reduction, 2-2 Pull Down
	Audio Performance	Equalizer, Subwoofer, Auto Volume Control (AVC),
	Other Control	PIP/POP, Canal+, Auto Progress System (APS), Aspect Ratio Control (ARC), Auto Picture Control (APC), Auto Sleep Timer, Auto Power Off
Power	Power supply	AC 100V ~ 240V , 50 / 60Hz
	Power Consumption	<260 W
Dimensions	W x H x D	1111.3mm x 632.3mm x 279.7mm
Weight (Net)	Without Accessories	31.5 kg

**Product specification and design are subject to change without notice.