

LCD TV PT3717

HD
ready




Abb. ähnlich


- Bildschirmdiagonale 37 Zoll (94 cm)
- Kontrast 800:1, Helligkeit 500cd/m²
- Auflösung 1366 x 768, 8ms
- Blickwinkel 176° / 176° (H/V)
- 3D Digital Comb Filter, NICAM Sound
- PAL, SECAM, NTSC, Teletext
- HD-ready, DVI-HDCP

Views	Section	Contents	PROTEK PT3717 HD ready	
	Display	Outline Dimension	877.0(H) mm X 516.8(V) mm	
		Active area	819.6(H) mm X 460.8(V) mm	
		Aspect Ratio	16:9	
		Pixel Pitch	0.200mm X 0.600mm X RGB	
		Resolutions	1,366 X RGB X 768	
		Viewing Angle(U/D/L/R)	R/L 176, U/D 176 (Angle free)	
		Colors	16.7M	
		Luminance	500 cd/m ²	
		Contrast Ratio	800 :1	
		Response Time	8 ms	
	System	Tuning	PAL- B/G ,D/K, I SECAM - B/G,D/K, L/L' NTSC- M	
		Audio	A2 STEREO NICAM STEREO	
		Speaker	Side 2 Speaker	
		Teletext	1000 Page	
		V-Chip/CCD	□(US)	
	Output	Audio	20W(10W + 10W) / RMS	
		Multi Language OSD	ENG/DEUT/FRA/ITA/ESP	
		Picture	16:9,4:3,Zoom,Panorama	
	Function	Function	4H Comb Filter Motion Adaptive De-interlace/Noise Reduction Edge Smooth/DLTI/DCI Film- Mode/Black Stretcher APC(Standard/Soft/Custom/Strong) ASC(Standard/Music/Movie/Speech /User/Surround Auto Power On,Off/Sleep Timer/On,Off Timer PIP/POP/DW	
		AV input	S - VHS (S-VIDEO)	
			AV1 (Full Scart or RCA)	
			AV2 (Half Scart or RCA)	
			Component Video (RCA Jack)	
			Audio L/R RCA Jack	
			PC Video input	D-Sub Jack / 15 Pin
			PC Audio input	Audio L/R RCA Jack
		DVI Input	-	
			Power	Input Voltage
consumption	Approx. 200W			
	Mechanical Size	Size (W x D x H) mm	1,076 X 240 X 638 (With Stand) 1,076 X 114 X 569.5(w/o stand)	
		Weight (N.Weight/ G.Weight)	28kg / 33.3kg	
	Container	20 Feet	60/56(W/O Pallets/With Pallets)	
		40 Feet	130/126(W/O Pallets/With Pallets)	
		40 Feet(Q)	130/126(W/O Pallets/With Pallets)	
	Accessory	Accessory	User Manual Remote Control incl. Battery Battery PC D-SUB cable(option)	

Accessories (optional)



Wallmount - fixed



Wallmount - flexible